



Item	Product	Plant Application	Order No.	Size of pack	pH-value ¹⁾	Description
------	---------	-------------------	-----------	--------------	------------------------	-------------

Standard products

		Pre-wash					
1	RM 802 ASF Intensive Dirt Remover	Prespraying HGV	6.290-082 6.290-083	25 l 200 l	11	Powerful alkaline dirt remover for heavily soiled, alkaline-resistant surfaces on commercial vehicles.	
2	RM 804 System Cleaner, red	Prespraying HGV	6.290-184 6.290-186	25 l 200 l	2	Acid cement, lime and mortar solvent for vehicles on construction sites.	
		Main wash					
3	RM 803 ASF HP Wash	Wheel washers, HP wheel wash HP gantry wash cars, HGV	Prespraying cars, HGV	6.290-084 6.290-085	25 l 200 l	10	Alkaline cleaner for prespraying and washing away road dirt, insects, oil-soot, brake dust. For cars and commercial vehicles.
	RM 805 System Cleaner, blue	HP gantry brush wash HGV	Prespraying HGV	6.290-187 6.290-189	25 l 200 l	11	Powerful alkaline cleaner for prespraying and for high-pressure cleaning. Removes road dirt, insects, oil-soot, brake dust, traffic film. For commercial vehicles.
5	RM 812 ASF Active Foam	Car gantry wash	Foam arch cars	6.290-089 6.290-090	25 l 200 l	8	Practically neutral cleaner formulated for brush wash. Also for use in foam arch to produce deep-acting and optically attractive foam. For cars.
6	RM 811 ASF Active Wash – compatible with wax	Brush wash cars, HGV		6.290-087 6.290-088	25 l 200 l	6	Practically neutral cleaner formulated for brush wash. Transports dirt away and is non-aggressive. For cars and commercial vehicles.
		Drying		Care			
7	RM 828 ASF Active Dryer	Drying cars, HGV	Hot wax cars, HGV	6.290-064 6.290-080	25 l 200 l	7	Waxes vehicle paintwork and immediately breaks down water film. Thermo-wax function; may be used hot or cold. For cars and commercial vehicles.
8	RM 829 Drying	Drying cars, HGV	Hot wax cars, HGV	6.290-101 6.290-080	25 l	7	Waxes vehicle paintwork and immediately breaks down water film. Thermo-wax function; may be used hot or cold. Specially for soft water (< 125 ppm) and osmosis water applications. For cars and commercial vehicles.

Special products

9	RM 822 ASF Foam Wax	Foam wax programme		6.291-172 6.291-872	25 l 200 l	7	Cold wax dries and shines using foam application method. Only for use with blower. For cars.
10	RM 830 ASF Underbody Wax	Underbody programme cars, HGV		6.291-176	25 l	7	Cold wax for temporary preservation after underbody wash. Excellent creeping properties. Contains no mineral hydrocarbons. For cars and commercial vehicles.
		Manual application					
11	RM 820 ASF Hot Wax	HDS machine preservation cars, HGV	Hot wax programme cars, HGV	6.291-170 6.291-870	25 l 200 l	7	Preservative with high carnauba wax content. Specially for application by hot water and high pressure. For cars and commercial vehicles.
12	RM 800 ASF Wheel Cleaner – intensive	Prespraying cars, HGV		6.290-086 6.291-747	25 l 200 kg	2	Acid cleaner for removing road dirt and brake dust from wheels. Specially for manual prespraying at entrance to vehicle wash. For cars and commercial vehicle.
13	RM 841 ASF Washing Bay and Tile Cleaner	Maintenance deep cleaning		6.290-081 6.291-762	25 l 200 kg	2	Acid deep-action maintenance cleaner for cleaning washing bays. Effectively removes limescale, grease, oil and other typical stains in washing bays.
14	RM 851 Disinfectant			6.291-298	30 kg	3	Bacteria reducer and deodorizer on hydrogen superoxide basis. For adding to industrial water recycling systems.

Products for self-service washes

		Main wash	Pre-wash				
15	RM 803 ASF HP Wash and Tile Cleaner	High-pressure brush wash	Schmutzlosen Fliegen- schmutz	6.290-084 6.291-085	25 l 200 l	10	Alkaline cleaner for prespraying and washing away road dirt, insects, oil-soot and brake dust with high pressure and brush.
16	RM 812 ASF Active Foam	Foam wash		6.290-089 6.290-090	25 l 200 l	8	Practically neutral cleaner formulated for foam wash with brush. Produces deep-acting and optically attractive foam.
		Drying		Care			
17	RM 820 ASF Hot Wax		Hot wax	6.291-170 6.291-870	25 l 200 l	7	Hot wax preservative with high carnauba wax content. Specially for application with hot water and high pressure.
18	RM 821 ASF Spray Wax	Preservation		6.291-171 6.291-871	25 l 200 l	8	Cold wax for temporary preservation. Waxes vehicle paintwork and immediately breaks down water film.

¹⁾ Approx. pH value of 1% solution in tap water